

SL6090 Series

sirius® lighting ATTO-DS Stem Pendant

Catalog No	

-		
lvne		
1700		

Project			
FIDIECL _			

Specifications/Features

Slim styling with excellent heat dissipation compliments any decor.

90° Vertical and 360° horizontal swivel for accent or downlighting applications. Solid grip lampholder.

Fixture can be further customized with accessories.

Fixture is milled from solid brass and finished in hand-polished chrome, platinum or 24K polished gold plate, smoked bronze or black.

Available in two different lengths: 3-1/2" and 9-3/4".

Mounting

SL: Standard rail mount. Allows the fixture to be conveniently mounted anywhere along the rail system up to the maximum capacity of the circuit.

(1) 50W (max.) MR16 FG lamp, GU5.3 base or compatible LED lamp (by otheres).

Available Finishes

- **C** Polished Chrome
- **PL** Platinum
- **B** Black





The sleek Black snoot extends 11/2" beyond the MR16 light source, all but eliminating glare.

Available for our ATTO and VARIAN Series fixtures.



6090DS: 3-1/2" **6250DS**: 9-3/4"

Rated for 12 volts.

Labels/Usage

CSA/ us Listed

Ordering Information

Example Order:	SL	6090DS	-	PL

Mounting **Fixture Finish 6090DS** - 3-1/2" SL - Rail Mounted Fixtures

6250DS - 9-3/4"

C - Polished Chrome PL - Platinum

B - Black

Light Control Accessories

LS Linear Spread Lens. Use with FASO-16 holder.

SL Soft Light (diffuser) Use with FASO-16 holder.

FA-16 Hex Cell Louver, Black Use with FASO-16 holder.

FAS-16 Natural Aluminum Accessory Holder.

Allows for Two Control Elements Max.

DS - Deco Snoot - Black

