

Specifications/Features

Fixture

Fixture is milled from solid brass and finished in hand-polished chrome, platinum or 24K polished gold plate.

Full selection of glass diffusers to compliment any decor. Sold separately. Stem fixture measures 17-1/4", not including glass

String fixture measures 39-1/4" long, not including glass; length is field adjustable.

Mounting

SL: Standard rail mount. Allows the fixture to be conveniently mounted anywhere along the rail system up to the maximum capacity of the circuit.




Lamp

(1) 20 - 50W T4 low pressure lamp, GY6.35 base or LED compatible lamp (by others)

(1) 50W (max.) MR16 FG lamp, GU5.3 base or LED compatible lamp (by others)

Rated for 12 volts.

Available Finishes

- C - Polished Chrome 
- PL - Platinum 
- B - Black 

Labels/Usage

CSA/us Listed



Ordering Information

Example Order: - -

Mounting	Fixture	Finish
<input type="text"/>	<input type="text"/>	<input type="text"/>

SL - Rail Mounted Fixtures

9500 - 17-1/4" L Stem Pendant
9100S - 39-1/4" L String Pendant, Field Adjustable

C - Polished Chrome
PL - Platinum
B - Black



Frosted Spot Glass Diffuser*

SL9010-F - 1-3/4" H x 2"



Tulip*

SL9006N - (CB, F, G, R, Y)
 3-1/2" H x 3-1/8" W

-CB (Cobalt Blue Satin), **-F** (Frosted),
-G (Green Satin), **-R** (Red Satin),
-Y (Yellow Satin)



SL9038-C - Crystal Glass Accents
 5-1/2" H x 3-3/16"



Large Tulip*

SL9037 - Clear Glass, Black Accents
 6-7/8" H x 3-3/16"



Fluted Tulip*

SL9016 - (CB, CC, F)
 3-1/4" H x 3-1/8" W

-CB (Cobalt Blue), **-CC** (Crystal Clear Glass), **-F** (Frosted Glass)

Use 50W (max.) Low pressure T4 Halogen or Xenon lamps (clear or frosted, with lamp shield) for all glass accessories, except where noted. Or LED Compatible Lamp (by others) *Also accepts 50W MR16 FG Lamp or LED Compatible Lamp (by others)