

Specifications/Features

Fixture

Fixture is milled from solid brass and finished in hand-polished chrome, platinum or 24K polished gold plate.

Full selection of glass diffusers to compliment any decor. Sold separately.

Stem fixture available in 2 different lengths: 17-1/4" and 37", not including glass
String fixture measures 41-15/16" long, not including glass; length is field adjustable.

Mounting

Three different mounting options allow for unlimited placement possibilities in lighting design:

SL: Standard rail mount. Allows the fixture to be conveniently mounted anywhere along the rail system up to the maximum capacity of the circuit.

Lamp

(1) 35W (max.) MR11 FG lamp, GZ4 base or compatible LED lamp (by others).(1) 50W (max.) MR16 FG lamp, GU5.3 base or compatible LED lamp (by others).(1) 20 - 50W T4 lamp, GY6.35 base or compatible LED lamp (by others). *Lamp choice dependant on glass shade selection. See Glass Accessories below for details and compatibility.* Rated for 12 volts.

Available Finishes

- C - Polished Chrome
- PL - Platinum
- B - Black



Labels/Usage

CSA/us Listed



Ordering Information

Example Order: -

Mounting

SL - Rail Mounted Fixtures

Fixture

1500 - 17-1/4" L Stem Pendant
1100 - 37" L Stem Pendant
1100S - 39-1/4" L String Pendant, Field Adjustable

Finish

C - Polished Chrome
PL - Platinum
B - Black



Frosted Spot Glass Diffuser*

SL9010-F - 1-3/4" H x 2"



Tulip*

SL9006N - (CB, F, G, R, Y)
3-1/2" H x 3-1/8" W
CB (Cobalt Blue Satin), **F** (Frosted),
G (Green Satin), **R** (Red Satin),
Y (Yellow Satin)



SL9038-C - Crystal Glass Accents
5-1/2" H x 3-3/16"



Large Tulip*

SL9037 - Clear Glass, Black Accents
6-7/8" H x 3-3/16"



Fluted Tulip*

SL9016 - (CB, CC, F)
3-1/4" H x 3-1/8" W
-CB (Cobalt Blue), **-CC** (Crystal Clear Glass), **F** (Frosted Glass)

Use 50W (max.) Low pressure T4 Halogen or Xenon lamps (clear or frosted, with lamp shield) for all glass accessories, except where noted.

*Also accepts 50W MR16 FG Lamp