

# SL50110 sirius® lighting TITAN

| Catalog No |  |
|------------|--|
|            |  |

| Type   |  |  |
|--------|--|--|
| IVDE — |  |  |

| Project |  |  |  |
|---------|--|--|--|

# Specifications/Features

### **Fixture**

 $90^{\circ}$  Vertical swivel and  $360^{\circ}$  horizontal swivel for accent or downlighting applications.

Fixture is milled from solid brass and finished in hand-polished chrome or platinum.

Length: 4-5/8"; Diameter: 2-1/8"

#### Mounting

**SL:** Standard rail mount. Allows the fixture to be conveniently mounted anywhere along the rail system up to the maximum capacity of the circuit.

#### Lamp

(1) 35W (max.) MR16 FG lamp, GU5.3 base or compatible LED lamp (by others).

#### **Available Finishes**

All finishes are hand-rubbed over solid brass

**C** - Polished Chrome

**PL** - Platinum

**B** - Black



Rated for 12 volts.

Labels/Usage CSA/us Listed



## **Ordering Information**

| Example Order: | SL 50110 - PL              |         |                      |  |  |
|----------------|----------------------------|---------|----------------------|--|--|
|                | Mounting                   | Fixture | Finish               |  |  |
|                |                            |         | -                    |  |  |
|                | SL - Rail Mounted Fixtures | 50110   | C - Polished Chrome  |  |  |
|                |                            |         | <b>PL</b> - Platinum |  |  |
|                |                            |         | B - Black            |  |  |